

SC2D

SCANNER BARCODE SERIE "SC2D"



Scanner barcode a pistola via cavo per utilizzo con indicatore di peso serie 3590 TOUCH SCREEN. Azionamento manuale tramite pulsante o automatico se installato sulla base di appoggio.

La soluzione ideale per
applicazioni industriali
avanzate

Caratteristiche:

- Luce LED per identificazione zona di scansione
- Feedback con segnale acustico
- Base di supporto inclusa in dotazione per utilizzo in modalità automatica
- OTTICA: CMOS area sensor
- DIMENSIONI in mm (lxwxh): 105 x 153 x 60 mm
- PESO: 115 g
- ALIMENTAZIONE: 5 Vdc da indicatore di peso
- LUNGHEZZA CAVO: 160cm
- PROTEZIONE: IP42
- AMBIENTE DI UTILIZZO: Temperatura da 5 a 50°C, Umidità max. 90% non condensante

Barcode supportati:

- Barcode (1D): UPC-A, UPC-E, UPC-E1, UPC-A Add-on , UPC-E Add-on, EAN-13, EAN-8, EAN-13 Add-on/EAN- 8 Add-on, JAN-8, JAN-13, Code 39, NW-7(Codabar), Industrial 2 of 5, Interleaved 2 of 5, Code 93, Code 128, GS1-128, MSI/Plessey, Code 11, OCR-B, GS1 DataBar, GS1 DataBar Limited ,GS1 DataBar Expanded, Composite GS1 DataBar, Composite GS1-128, Composite EAN, Composite UPC , TELEPEN
- Barcode (2D): PDF417, MicroPDF417, Codablock F, QR Code, Micro QR Code, DataMatrix (ECC 200), MaxiCode, Aztec Code, Chinese Sensible Code

PARTICOLARE 1



PARTICOLARE 2



PARTICOLARE 3





www.diniargeo.com

“YOUR WORLDWIDE PARTNER FOR WEIGHING,”

DINI ARGEO
FRANCE sarl
France

DINI ARGEO
GMBH
Germany

DINI ARGEO
UK Ltd
United Kingdom

DINI ARGEO WEIGHING
INSTRUMENTS Ltd
China

DINI ARGEO
OCEANIA
Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 843418

SERVICE ASSISTANCE

Via Dell'Elettronica, 15
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 921784

SALES AND TECHNICAL ASSISTANCE SERVICE